

WOOD GOLF CLUB

CROSS REFERENCE TO RELATED APPLICATIONS

Drs 1517
[0001] This application is a continuation-in-part application of U.S. Appl. No. 09/395,664 filed on September 14, 1999, now pending.

BACKGROUND OF INVENTION

Field of the Invention

[0002] The present invention relates to a hollow, metallic wood golf club, called a metal wood, particularly to the structure of a head thereof.

Prior Art

[0003] A head of a so-called metal wood club is constructed of metallic shell members made for example of titanium, thus defining a hollow interior. The hollow interior is, depending on cases, filled with foaming resin, such as hard urethane foam.

[0004] A golf club head is subjected to elastic deformation due to impact developed by striking balls. For conventional golf clubs, a face shell, a crown shell and a sole shell would be all elastically deformed due to the impact. As a face is to contact balls, elastic forces due to the deformation thereof will contribute to enhancing the initial travelling speed of balls and elongating the travelling distances thereof. Accordingly, a face need to be effectively deformed. For the deformation of a sole and a crown which construct a head body, however, the deformation thereof will hinder the effective deformation of the face, so that so-called loss of power would take place. Thus, rigid soles and crowns are desirable.

[0005] Conventionally, there is proposed a metal wood head in Japanese Patent Un-Examined Publication No.60-36074, in which a nearly L-shaped reinforcing member is welded to the inside of shells along a sole and a face. Further, US Patent No.5,467,983 to Chen discloses that a face reinforcing member is provided on a rear surface of the face to reinforce the same. With such reinforcing member, however, not only a head body but also a face is

038796-053601

[0012] To ensure the suppressing of the deformation of the body portion of the head, the reinforcing member should be positioned in the vicinity of the intermediate position between the face and the rearmost side of the head. In the event that the shaft connecting portion of the head becomes an obstacle to providing the reinforcing members, yet the reinforcing members may be provided in a range of $\pm 20\%$ of a distance defined from the face to a rearmost side of the head, with an intermediate position between the face to the rearmost side of the head being assumed to be a reference position, whereby the deformation of the body portion of the head can be suppressed effectively enough.

[0013] Other objects, features and advantages of the invention will be apparent to those skilled in the art from the following description of the preferred embodiments of the invention, wherein reference is made to the accompanying drawings, of which:

3

[0015] Fig. 2 is a partially cutaway perspective view showing a wood golf club of Fig. 1.

[0016] Fig. 3 is an exploded perspective view showing a wood golf club of Fig. 1.

[0017] Fig. 4 is a partially cutaway perspective view showing a wood golf club in accordance with a second embodiment of the invention.

[0018] Fig. 5 is a section of a wood golf club of Fig. 4.

[0019] Fig. 6 is a section showing a wood golf club in accordance with a third embodiment of the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0020] Hereinafter is explained a first embodiment of the invention with reference to Figs. 1 through 3.

[0021] A wood golf club according to the present embodiment has a head 1 which is hollow and metallic, and thus it is a so-called metal wood. The head 1 comprises a ball-striking face 2 on its front face, a back 3 on its back, a sole 4 in its lower part, a crown 5 in its upper part, a toe 6 at one side and a heel 7 at an other side, respectively. The upper portion of the heel 7 is formed with a neck 8, from which extends obliquely upwards a hosel 9. The hosel 9 serves as a shaft connector for connecting a shaft 10 thereto. The head 1 has a hollow interior 11, which may be filled with filler such as polyurethane. The face 2 is formed with a plurality of grooves called score lines 12.

[0022] The outer shell of the head 1 consists of two pieces, i.e., a front piece or face shell member 16 and a back piece or body shell member 17. Between the shell members 16 and 17 is provided a plate member 18 which is plate-shaped or tabular. These shell members 16, 17 and the plate member 18 are formed from a metal such as titanium or titanium alloy, which are each formed by suitable means such as press-working including forging, casting or machining so that they are joined together by welding or the like.

[0023] The face shell member 16 makes up the face 2, the front and minority portions of the sole 4 and the crown 5 as well as the neck 8 and hosel 9, which is open towards a rear side, being receptacle-shaped. The body shell

member 17 makes up the body portion of the head 1, namely, the back 3 and the back and majority portions of the sole 4 and the crown 5, which is open towards a front side, being also receptacle-shaped. The reason for having allowed the face shell member 16 to make up the front portions of the sole 4 and the crown 5 is to have the same shell member 16 make up the neck 8 and the hosel 9 as well, and thus the transverse dimension of the face shell member 16 is set at minimum value to construct the neck and the hosel 9.

[0024] The aforesaid plate member 18 is frame-shaped, having an opening 19 in the center thereof, and the width "w" thereof is greater than the thickness "t" of the shell members 16 and 17, as shown in Fig. 3. As the external configurations of the shell members 16, 17 and the plate member 18 shall be the same as far as the portions where they are joined together are concerned, the inner peripheral portion of the plate member 18 is allowed to project toward the hollow interior 11, thereby constructing a reinforcing member 20. The reinforcing member 20 is so shaped that it may be provided nearly along a cross-sectional area of the hollow interior 11 defined in a toe to heel direction, a certain distance away from the face 2, and thus makes up 20 % or more of the cross-sectional area. In addition, the reinforcing member 20 is positioned in the vicinity of the intermediate position between the face 2 and the rearmost side of the back 3. Preferably, the reinforcing member 20 is positioned in a range of $\pm 20\%$ of a distance defined from the face 2 to a rearmost side of the head 1, with an intermediate position between the face 2 to the rearmost side of the head 1 being assumed to be a reference position. More specifically, the distance from the face 2 to the rearmost side of the head 1 is defined as a distance from a tip end of a leading edge to the rearmost end of the back 3, assuming that the face angle is zero degree.

[0025] Hereinafter is explained how the above-mentioned structure actually works. At the time of impact or when a ball is struck on the face 2, the portions positioned rearwardly of the reinforcing member 20 is less subjected to deformation due to the same. In other words, the sole 4 and the crown 5 which construct the body portion of the head 1 are rigidly supported by the reinforcing member 20, thus suppressing the deformation thereof.

Accordingly, the unnecessary deformation of the head body is prevented so that energy generated at the time of ball-impact is dedicated to the deformation of the face 2 of the face shell member 16. As a result, the face 2 is elastically deformed in an effective manner, thereby realizing greater initial travelling speed of balls as well as elongated travelling distances of balls.

[0026] Generally speaking, to ensure the suppressing of the deformation of the body portion of the head 1, the reinforcing member 20 should be positioned in the vicinity of the intermediate position between the face and the rearmost side of the head. Further, as a certain space or clearance is necessary between the face 2 of the face shell member 16 and the reinforcing member 20 in order to allow the face 2 to deform elastically enough to impart suitable elastic force to struck balls, a space adjacent to the rear surface of the face 2 is kept hollow so that any member may not contact the same. Further, as the reinforcing member 20 is frame-shaped in the present embodiment, the interior of the head 1 is not partitioned by anything so that it may define a continuous hollow space.

[0027] Incidentally, in the event that the shaft connecting portion of the head 1 becomes an obstacle to providing the reinforcing members 20, yet the reinforcing members 20 may be provided in a range of $\pm 20\%$ of a distance defined from the face 2 to a rearmost side of the head 1, with an intermediate position between the face 2 to the rearmost side of the head 1 being assumed to be a reference position, whereby the deformation of the body portion of the head can be suppressed effectively enough.

[0028] Further, as the reinforcing member 20 is frame-shaped, the reinforcing member 20 can be lightened, thus realizing the lightening of the whole head 1. As a result, the head 1 can be large-sized through the lightening of the head 1. If the head 1 is large-sized, then the area of the face 2 will be increased, thus enlarging so-called sweet area. On the other hand, if the reinforcing member 20 is frame-shaped, then the above-mentioned deformation-suppression effect would decrease. Therefore, the reinforcing member 20 should desirably make up 20% or more of the cross-sectional area

[illegible]

[0034] With the two reinforcing members 20 thus provided, the reinforcing effect will be further enhanced, thereby more effectively suppressing the deformation of the body portion of the head such as the sole 4 and the crown 5. It should be noted that the number of the reinforcing members does not have to be limited to either one, as proposed in the first and second embodiments, or two as in the third embodiment, but may be three or more. In the event that a plurality of reinforcing members are provided, they are to be arranged from front toward back.

[0035] Incidentally, the present invention should not be limited to the foregoing embodiments, but may be modified within a scope of the invention. For example, whilst the shell members 16 and 17 that construct the outer shell of the head 1 are separate from the plate members 18, 21 that construct the reinforcing members 20, 22 in the foregoing embodiments, the reinforcing members can be formed integrally with the shell members that construct the outer shell of the head, if the outer shell of the head is for example constructed by the increased number of the shell members. For example, one of the reinforcing members 20 in the third embodiment may be formed integrally with the aforesaid intermediate first body shell member 17a. Further, whilst the outer shell of the head 1 is divided in a manner that takes the positions of the plate members 18, 21 as a boundary so that the plate members 18, 21 are sandwiched between the respective shell members 16, 17, 17a and 17b in the foregoing embodiments, the positions where the outer shell of the head is to be divided should not always correspond with those of the reinforcing members, but the reinforcing members may be joined to the inside of the shell members. It should be noted, however, that the above-mentioned divisional structure according to the foregoing embodiments would make the manufacture of a golf club easier.